

UNITED STATES PATENT APPLICATION FOR

EMBEDDING WEB ACCESS FUNCTIONALITY INTO
A DEVICE FOR USER INTERFACE
FUNCTIONS

Inventors:

Chandrasekar Venkatraman
Jeffrey A. Morgan

0962304 052304
102250 10929960

IN 3 AI

BACKGROUND OF THE INVENTION

Field of Invention

5 The present invention pertains to the field of
user interfaces for devices. More particularly, this
invention relates to embedding web access
functionality into devices to provide enhanced and
widely accessible user interface functions.

10

Art Background

 A wide variety of devices including office
equipment, home-based equipment, and lab equipment,
as well as a variety of other types of devices
15 commonly provide device specific user interface
functions. Such devices may also be referred to as
gadgets. Office equipment includes, for example,
printers, fax machines, copiers, and various types of
communication and telephony devices. Home-based
20 devices include home entertainment equipment such as
televisions and video and audio players and recorders
as well as security systems, automobiles, appliances,
thermostats, and hot tubs. Lab equipment includes
measurement devices such as oscilloscopes, spectrum
25 analyzers and other types of measurement equipment as
well as networking equipment.

 The user-interface mechanisms of such devices
commonly include relatively simple and low cost user

09662804.052204

input and display mechanisms. Such simple mechanisms may include, for example, light emitting elements such as LED/LCD elements as well as various types of simple input buttons or switches. Such simple mechanisms are typically constructed to be low cost to minimize the overall cost of such devices. In addition, such mechanisms are usually compact and enable relatively small sizes for such devices. Unfortunately, such simple user interface mechanisms severely limit the range and flexibility of the user interface functions provided by such devices.

The user-interface functions of such a device may be enhanced by the implementation of a screen-based user interface mechanism within the device. For example, such a device may include a display screen, and a rendering processor along with appropriate software for generating a rich graphical user interface suitable for the particular type of device. However, such screen displays and rendering mechanisms are usually expensive and increase the overall cost of the device. Such high costs are typically unsuitable for lower cost devices targeted for a relatively large mass market. Moreover, display screens and associated hardware may be too bulky for the size constraints of many devices.

09862804-052204
T02250-10829860

A screen-based user interface may be provided for a device using an external computer system. For example, the device may be connected to the computer system through either a standard connection such as a serial or parallel port connection or through a specialized hardware interface. The external computer system usually executes a set of software for communication and user interface to the device. The external computer system may implement a screen-based user interface for the device. The external computer system may also execute web server software that enables external web browsers to access the computer system and in turn the user interface of the device.

Unfortunately, such an external computer system greatly increases the cost of providing a screen-base user interface for a device. In addition, such prior computer system based solutions usually require the development of specialized software for each particular type of device. Moreover, such specialized software for a particular device from a particular manufacturer must typically be developed for differing types of computer system platforms. Such a variety of differing software for differing platforms greatly complicates the task of providing support for the devices. Furthermore, the development and support costs of such a variety of

software usually increase the overall cost of providing a screen based user interface for such devices.

102250 10829860

variety of devices without the necessity to develop
expensive hardware and software applications for
differing devices. The present methods and
mechanisms employ web technology so that access to a
5 device user interface is independent of the computer
system platform employed and independent of the web
browser software executed and independent of the
location of the user.

10 The user interface information is packaged using
the Hyper-Text Markup Language (HTML) and is
transported according to the Hyper-Text Transfer
Protocol (HTTP). The HTML and HTTP protocols enable
communication with existing web browsers independent
15 of the platform that executes the web browser. The
present techniques avoid the need of an industry-wide
Application Programming Interface (API) to unify the
control and use of equipment.

20 Other features and advantages of the present
invention will be apparent from the detailed
description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is described with respect to particular exemplary embodiments thereof and
5 reference is accordingly made to the drawings in which:

10 **Figures 1a-1b** illustrate a device with embedded web access functionality that provides device-specific user interface functions through a device web page;

15 **Figure 2** shows a home-based network that enables a web browser to access the user interface functions through the device web page;

Figure 3 illustrates an example device web page for a printer device;

20 **Figure 4** shows a large organization network or intranet that enables access to the device web pages of differing devices;

25 **Figure 5** illustrates access to device web pages through the Internet world-wide web.

DETAILED DESCRIPTION

Figure 1a illustrates a device 10 with embedded web access functionality that provides device-specific user interface functions. The device 10 includes a network interface 12 and a web server 14 along with a monitor 16. The network interface 12 enables communication via a communication path 22. The monitor 16 controls various device-specific functions of the device 10 and monitors a set of information pertaining to the device 10 via a control/monitor path 20. The web server 14 provides web server functions to web clients via the communication path 22. The web server 14 provides web server functions according to the Hyper-Text Transfer Protocol (HTTP).

The web server 14 receives HTTP commands through the network interface 12 that specify a predetermined Universal Resource Locator (URL) for the device 10. The HTTP commands may be used by web clients to read information from the device 10 such as device status information. The HTTP commands may also be used to transfer information to the device 10 such as information that controls the functions or operating states of the device 10. Such HTTP commands include HTTP GET, HTTP POST, and HTTP PUT commands.

In response to an HTTP command targeted for the device 10, the web server 14 generates a web page 18 that defines a set of user interface functions for the device 10. The web page 18 is a Hypertext Markup Language (HTML) file. The network interface 12
5 transfers the web page 18 to a requesting HTTP client via the communication path 22.

The web server 14 generates the web page 18
10 dynamically to reflect the updated state of the information pertaining to the device 10 that is maintained by the monitor 16. The web page 18 may also define control buttons according to the HTTP protocol that enable various control functions for
15 the device 10 to be initiated from a web client via the communication path 22. The web page 18 may contain text, images, multimedia files, forms, tables or any object type supported by the HTTP and HTML protocols.

20

In addition, the web page 18 may contain one or more URLs that specify additional web pages located within the device 10. The web page 18 may also contain one or more URLs that specify additional web
25 pages located elsewhere, i.e. external to the device 10. The additional web pages external to the device 10 may be located, for example, on a local

communication network or on the Internet world wide web.

5 The device 10 represents a wide variety of devices including devices such as printers, fax machines, copiers, communication and telephony devices, home entertainment devices such as televisions, video and audio devices as well as appliances such as refrigerators and washing
10 machines, security systems, automobiles, and hot tubs. The device 10 also represents a variety of measurement instruments including oscilloscopes, and spectrum analyzers and other types of measurement devices. In addition, the device 10 represents a
15 variety of computer peripheral devices including mass storage units such as rotating media storage units.

20 The communication path 22 represents any communication means that is capable of transferring HTML files according to the HTTP web protocol. The communication path 22 may be realized by a wide variety of communication mechanisms including local area networks, telephone lines including cellular telephone links, serial communication links, parallel
25 communication links, power line communication links, and radio and infrared communication links. The communication path 22 may also be a direct Internet connection to the world-wide web.

Figure 1b is a hardware block diagram of the device 10. The device 10 includes a processor 200, a memory 210, a set of device-specific hardware 300 along with a set of input/output circuitry 220 that enables communication via the communication path 22. The processor 200 performs device-specific functions for the device 10 in combination with the device-specific hardware 300. The processor 200 is also employed to provide web server functionality in the device 10. In one embodiment, the processor 200 stores the web page 18 in the memory 210 which may also be used to store information associated with normal device-specific functions.

In one embodiment, the device 10 is a printer device wherein the processor 200 and the memory 210 preform image rendering functions and the device-specific hardware 300 includes printer hardware and associated circuitry and wherein the input/output circuitry 220 provides network access to the printer device 10. The web server functionality is embedded into the printer device 10 by providing software or firmware for the processor 200 and by utilizing space available in the memory 210 and by using the existing input/output circuitry 220 such as Ethernet circuitry to transfer HTML files.

In another embodiment, the device 10 is a video player/recorder wherein the processor 200 and the memory 210 perform functions for reading video and audio information from and writing video and audio information to a storage media such as magnetic tape or an optical storage media. The device-specific hardware 300 includes media actuation hardware such as motors and magnetic heads and associated circuitry for reading and imparting information onto the storage media. The web server functionality is embedded into the video device 10 by providing software or firmware for the processor 200 and by utilizing space available in the memory 210 and by adding the input/output circuitry 220 to the video device 10.

In yet another embodiment, the device 10 is a washing machine wherein the processor 200 and the memory 210 perform functions for controlling wash cycles. The device-specific hardware 300 includes hardware such as motors, valves, sensors, and associated circuitry. The web server functionality is embedded into the washing machine 10 by providing software or firmware for the processor 200 and by utilizing space available in the memory 210 and by adding the input/output circuitry to the video device 10.

10829850-0520-10829850

Sub
A 20

5

15

25

controller module or control computer contained in an

automobile. The input/output circuitry 220 such as cellular transmitter/receiver circuitry enables a web browser to access control and status information for the automobile which is contained in the web page 18.

5

In another embodiment, the device 10 is a mass storage device such as a disk drive or CD-ROM drive. The input/output circuitry 220 such as local area network interface circuitry enables a web browser to access control and status information for the mass storage device which is contained in the web page 18.

10

In yet another embodiment, the device 10 is a home-entertainment device such as an audio system. The input/output circuitry 220 such as infrared communication circuitry or power line communication circuitry enables a web browser such as a home computer to access control and status information for the audio system which is contained in the web page 18.

15

20

The memory 210 may be a static memory such as read-only memory, a flash memory, or a disk drive or may be a volatile memory such as a random access memory. The web page may be stored in the static memory or the random access memory in the HTML format or may be generated on the fly without being stored in the device 10.

25

09862804 05201
T02250 40829860

Figure 2 shows a home-based network 30 that enables a web browser 40 to access the user interface functions of the device 10. The home-based network 30 may be implemented with a variety of communication mechanisms suitable for a home including power line communication links, twisted pair communication links, radio frequency communication links, and infrared communication links.

The web browser 40 includes a display 42 for generating visual objects including text, images, multimedia objects, and graphical user interface objects. The web browser 40 includes a selection device 44 that enables a user to select objects and URL links rendered on the display 42. The web browser 40 may also include an audio capability that enables rendering of audio information to the user.

The home-based network 30 may also enable communication among a set of devices 50-52. The devices 50-52 may include devices such as home appliances, home security systems, home entertainment devices, air-conditioning systems and hot-tubs. Any of the devices 50-52 that implement the device web page mechanisms disclosed herein may provide device specific user interface web pages to the web browser 40 via the home-based network 30.

The web browser 40 may be embodied in a computer system that executes a set of web browser software. Such a computer system with web browser functionality may be realized by any one of a variety of available computer system platforms including Windows
5 platforms, Macintosh platforms, Unix platforms as well as any other platform capable of executing web browser software that provides HTTP client functions and that renders HTML files.

10

The web browser 40 may also be embodied in a variety of other devices that provide HTTP client functions and that render HTML files. Such devices include specialized hardware designed for television
15 or telephone systems as well as low cost web browser devices and network computers.

20

A user accesses and controls the user interface functions of the device 10 using the web browser 40. The user enters a URL corresponding to the device 10 into the web browser 40. In response, the web browser 40 transfers an HTTP command which includes the entered URL over the home-based network 30. The device 10 receives the HTTP command via the
25 communication path 22 and recognizes the URL contained therein.

In one embodiment, the information for the web page 18 is periodically updated by the processor 200 and is stored in HTML format in the memory 210. In such an embodiment, the processor 200 reads the web page 18 from the memory 210 in response to the HTTP command and transfers the web page 18 to the web browser 40 via the home based network 30.

In an alternative embodiment, the processor 200 generates the web page 18 on the fly in response to the HTTP command from the web browser 40. In such an embodiment, the processor 200 obtains information pertaining to the device from the device-specific hardware 300 after receiving the HTTP command and recognizing the URL contained therein. The processor 200 formats the information into the HTML format that defines the web page 18 and transfers the HTML formatted information to the web browser 40 via the home based network 30.

The HTML file is transferred according to the HTTP protocol which specifies the URL corresponding to the web browser 40. The web browser 40 receives the HTML file and renders the web page 18 on the display 42.

The following is an example HTML file that defines the web page 18 in an embodiment wherein the device 10 is a printer device.

5 <TITLE>Printer Home Page</TITLE>
 <H1>home page for device 10</H1>
 <HR>
 The following information pertains to
 the device 10 which in this example
10 is a printer
 <table border>
 <caption> Printer with a URL </caption>
 <TR>
 <TD>Printer Name</TD>Port 9</TD>
15 </TR>
 <TR>
 <TD>Administrator</TD><TD>Mr. John Doe</TD>
 </TR>
 <TR>
20 <TD>Location</TD><TD>Building 1U</TD>
 </TR>
 </TABLE>
 <P>
 Service Contract
25 <P>
 Supplies
 ordering
 <P>
 Future
30 Products
 <P>
 <HR>

35 **Figure 3** illustrates the web page 18 for the
 example HTML file shown above wherein the device 10
 is a printer. The web page 18 is rendered on the
 display 42 by the web browser 40 in response to the
 example HTML code set forth above. The web page 18

includes a page title 70, a header section 60, a set of ASCII text 62, a table section 64, and a set of hyperlinks 66-68.

5 The page title 70 is defined by the HTML
 <TITLE>Printer Home Page</TITLE> coding shown above.
 The header section 60 is defined by the HTML code
 <H1>Home Page for device 10</H1> in the HTML file
10 shown above. The ASCII text 62 is the ASCII text
 contained in the HTML file shown above. The table
 section 64 is defined with coding in the HTML file
 shown above and provides information pertaining to
 the printer including a printer name, an
 administrator, and a location for the printer.

15 The hyperlinks 66-68 defined in the HTML file
 shown above direct the web browser 40 to other web
 pages for various printer support functions. For
 example, the hyperlink 66 "Service Contract" may be
20 selected by the user with the selection device 44 to
 direct the web browser 40 to the URL
 "http://www.hpssc.com" for information regarding
 printer service contracts. Similarly, hyperlinks 67
 and 68 provide links to web pages for ordering
25 printer supplies and obtaining information for future
 printer products from the manufacturer of the printer
 device 10.

Sub
A5

The web page 18 for the printer may also include manuals, parts lists, and other associated publications. These publication may be stored within the device 10 in, for example, a nonvolatile memory, or may be referenced elsewhere via hyperlinks contained in the web page 18. These publications contain dynamic information such as updated manuals as well as new and updated software driver routines for the device 10.

Figure 4 shows a large organization network 80 that enables access to the device web pages of the device 10 and the devices 50-52. The large organization network 80 may be referred to as an Intranet and may be implemented with a variety of communication mechanisms including local area networks connected together by various types of communication links.

Any one or more of a set of computer systems 90-92 coupled to the large organization network 80 may access the device web pages of the devices 10 and 50-52. The computer systems 90-92 may execute one or more of a variety of available web browser software or may have web browser functions built in.

A user of one of the computer systems 90-92 enters a URL corresponding to the desired one of the

devices 10 and 50-52 into the corresponding web browser application. In response, the particular web browser application as an HTTP client transfers an HTTP command that specifies the desired URL over the large organization network 80. The device specified by the HTTP command recognizes the URL contained therein. In response, the targeted device transfers an HTML file that defines its device web page via large organization network 80. The transfer of the HTML file specifies the URL of the originating HTTP client computer system from among the computer systems 90-92. The originating HTTP client computer system recognizes its URL and receives and then renders the device web page to the user.

Figure 5 illustrates access to device web pages through a direct Internet connection to the world-wide web 100. The web page 18 of the device 10 may be accessed by any web client on the world-wide web 100 including the web browser 40.

In addition, a communication system 102 functions as a communication bridge between the world-wide web 100 and a local area network 120 and a communication system 104 functions as a communication bridge between the world-wide web 100 and a home base network 130. As a consequence, any other HTTP clients coupled to the local area network 120 or the

home-base network 130 may access the device web pages in a device 108, a device 106, or the device 10. In addition, the web browser 40 or any HTTP client on the world-wide web 100 may access the device web pages of the devices 106 and 108.

The embedded web server functionality described herein enables a variety of widely accessible device interrogation and control functions for a particular device as well as for sets of devices. For example, a web page may be embedded into each washing machine of a chain of Laundromats wherein an operator from an office computer can determine the machines that require servicing and schedule daily service routing to the Laundromats accordingly.

The foregoing detailed description of the present invention is provided for the purposes of illustration and is not intended to be exhaustive or to limit the invention to the precise embodiment disclosed. Accordingly, the scope of the present invention is defined by the appended claims.

09862804.052204